

## MEDIUM DUTY ELASTOMER/ TYPE: SJEOW

• Thermoplastic Elastomer Jacket • 300 V Cord • UL Listed • CUL Listed • Outdoor Usage

PART NUMBER	AWG SIZE	# COND.	UL TYPE	STRAND	MAX. VOLT	AMPS	TEMP. RATING	CORD O.D.	RET. LGTH. FT.	PRIMARY COND. COLOR	COIL O.D.	LBS / CORD
4-9121-89-96W	16	5	SJEOW	65/34	300	8	105	.440	2	WE, OE, GN, RD, BK	1.63	1.99
4-9121-00-96W	16	5	SJEOW	65/34	300	8	105	.440	4	WE, OE, GN, RD, BK	1.63	3.91
4-9121-87-96W	16	5	SJEOW	65/34	300	8	105	.440	6	WE, OE, GN, RD, BK	1.63	5.82
4-9121-88-96W	16	5	SJEOW	65/34	300	8	105	.440	8	WE, OE, GN, RD, BK	1.63	7.73
4-9122-89-96W	16	6	SJEOW	65/34	300	8	105	.485	2	WE, OE, GN, RD, BE, BK	1.72	2.28
4-9122-00-96W	16	6	SJEOW	65/34	300	8	105	.485	4	WE, OE, GN, RD, BE, BK	1.72	4.43
4-9122-87-96W	16	6	SJEOW	65/34	300	8	105	.485	6	WE, OE, GN, RD, BE, BK	1.72	6.61
4-9122-88-96W	16	6	SJEOW	65/34	300	8	105	.485	8	WE, OE, GN, RD, BE, BK	1.72	8.75

## HEAVY DUTY ELASTOMER / TYPE: SEOW

• Thermoplastic Elastomer Jacket • 600 V Cord • UL Listed • CUL Listed • Outdoor Usage

PART NUMBER	AWG SIZE	# COND.	UL TYPE	STRAND	MAX. VOLT	AMPS	TEMP. RATING	CORD O.D.	RET. LGTH. FT.	PRIMARY COND. COLOR	COIL O.D.	LBS / CORD
4-9123-89-96W	18	3	SEOW	41/34	600	7	105	.385	2	WE, GN, BK	1.33	1.28
4-9123-00-96W	18	3	SEOW	41/34	600	7	105	.385	4	WE, GN, BK	1.33	2.43
4-9123-87-96W	18	3	SEOW	41/34	600	7	105	.385	6	WE, GN, BK	1.33	3.62
4-9123-88-96W	18	3	SEOW	41/34	600	7	105	.385	8	WE, GN, BK	1.33	4.8
4-9124-89-96W	18	4	SEOW	41/34	600	7	105	.415	2	WE, GN, RD, BK	1.455	1.64
4-9124-00-96W	18	4	SEOW	41/34	600	7	105	.415	4	WE, GN, RD, BK	1.455	3.17
4-9124-87-96W	18	4	SEOW	41/34	600	7	105	.415	6	WE, GN, RD, BK	1.455	4.73
4-9124-88-96W	18	4	SEOW	41/34	600	7	105	.415	8	WE, GN, RD, BK	1.455	6.28
4-9125-89-96W	16	3	SEOW	65/34	600	10	105	.415	2	WE, GN, BK	1.455	1.64
4-9125-00-96W	16	3	SEOW	65/34	600	10	105	.415	4	WE, GN, BK	1.455	3.17
4-9125-87-96W	16	3	SEOW	65/34	600	10	105	.415	6	WE, GN, BK	1.455	4.73
4-9125-88-96W	16	3	SEOW	65/34	600	10	105	.415	8	WE, GN, BK	1.455	6.3
4-9126-89-96W	16	4	SEOW	65/34	600	8	105	.445	2	WE, GN, RD, BK	1.64	2.14
4-9126-00-96W	16	4	SEOW	65/34	600	8	105	.445	4	WE, GN, RD, BK	1.64	4.18
4-9126-87-96W	16	4	SEOW	65/34	600	8	105	.445	6	WE, GN, RD, BK	1.64	6.16
4-9126-88-96W	16	4	SEOW	65/34	600	8	105	.445	8	WE, GN, RD, BK	1.64	8.2
4-9127-89-96W	16	6	SEOW	65/34	600	8	105	.575	2	WE, OE, GN, RD, BE, BK	2.025	3.03
4-9127-00-96W	16	6	SEOW	65/34	600	8	105	.575	4	WE, OE, GN, RD, BE, BK	2.025	5.95
4-9127-87-96W	16	6	SEOW	65/34	600	8	105	.575	6	WE, OE, GN, RD, BE, BK	2.025	9.01
4-9127-88-96W	16	6	SEOW	65/34	600	8	105	.575	8	WE, OE, GN, RD, BE, BK	2.025	11.73
4-9128-89-96W	14	4	SEOW	41/30	600	12	105	.590	2	WE, GN, RD, BK	2.055	3.16
4-9128-00-96W	14	4	SEOW	41/30	600	12	105	.590	4	WE, GN, RD, BK	2.055	6.22
4-9128-87-96W	14	4	SEOW	41/30	600	12	105	.590	6	WE, GN, RD, BK	2.055	9.3
4-9128-88-96W	14	4	SEOW	41/30	600	12	105	.590	8	WE, GN, RD, BK	2.055	12.27

### WHITNEY BLAKE ELASTOMER CORDS:

Elastomer coiled cords offer great flexibility in use, ranging from medical equipment to communication products.

Each design features a strong, yet flexible thermoplastic elastomer jacket and are UL and CUL listed for outdoor use.

Medium (SJEOW) and Heavy Duty (SEOW) varieties include multiple length options and sizes based on your project requirements.

Reach out to us today for a quote - we look forward to supporting your project needs.