

LIGHT DUTY / TYPE: SVO

- Neoprene Jacket
- 300 V Cord
- UL Listed
- CSA Certified

PART NUMBER	AWG SIZE	# COND.	UL TYPE	STRAND	MAX. VOLT	AMPS	TEMP. RATING	CORD O.D.	RET. LGTH. FT.	PRIMARY COND. COLOR	COIL O.D.	LBS / CORD
4-8001-00-91	18	2	SVO	41/34	300	7	60	.260	4	BK, W	.875	1.15
4-8001-89-91	18	2	SVO	41/34	300	7	60	.260	2	BK, W	.875	.63
4-8003-00-91	18	3	SVO	41/34	300	10/7	60	.275	4	BK, W, G	1.00	1.46
4-8003-89-91	18	3	SVO	41/34	300	10/7	60	.275	2	BK, W, G	1.00	.87

MEDIUM DUTY / TYPE: SJOW

- Neoprene Jacket
- 300 V Cord
- UL Listed
- CUL Listed
- CSA Certified

PART NUMBER	AWG SIZE	# COND.	UL TYPE	STRAND	MAX. VOLT	AMPS	TEMP. RATING	CORD O.D.	RET. LGTH. FT.	PRIMARY COND. COLOR	COIL O.D.	LBS / CORD
4-8011-00-91W	18	2	SJOW	41/34	300	10	90	.320	4	BK, W	1.19	1.75
4-8011-89-91W	18	2	SJOW	41/34	300	10	90	.320	2	BK, W	1.19	1.03
4-8013-00-91W	18	3	SJOW	41/34	300	10/7	90	.350	4	BK, W, G	1.25	2.3
4-8013-89-91W	18	3	SJOW	41/34	300	10/7	90	.350	2	BK, W, G	1.25	1.3
4-8014-00-91W	18	4	SJOW	41/34	300	7/5.6	90	.380	4	BK, W, R, G	1.31	2.13
4-8014-89-91W	18	4	SJOW	41/34	300	7/5.6	90	.380	2	BK, W, R, G	1.31	1.5
4-8015-00-91W	18	5	SJOW	41/34	300	7/5.6	90	.440	4	BK, W, R, G, OE	1.63	4.1
4-8015-89-91W	18	5	SJOW	41/34	300	5.6	90	.440	2	BK, W, R, G, OE	1.63	2.08
4-8017-00-91	18	7	*	41/34	300	4.9	60	.500	4	BK, W, G, R, BE, BN, Y	1.88	4.4
4-8017-89-91	18	7	*	41/34	300	4.9	60	.500	2	BK, W, G, R, BE, BN, Y	1.88	2.6
4-8008-00-91	18	15	**	41/34	300	4.9	60	.575	4	BK, W, G, R, OE	2.03	6.6
4-8008-89-91	18	15	**	41/34	300	4.9	60	.575	2	BE, Y, BN, SE, PE	2.03	3.8
4-8022-00-91W	16	2	SJOW	65/34	300	13	90	.360	4	BK, W	1.25	2.27
4-8022-89-91W	16	2	SJOW	65/34	300	13	90	.360	2	BK, W	1.25	1.3
4-8023-00-91W	16	3	SJOW	65/34	300	13/10	90	.385	4	BK, W, G	1.31	2.72
4-8023-89-91W	16	3	SJOW	65/34	300	13/10	90	.385	2	BK, W, G	1.31	1.5
4-8024-00-91W	16	4	SJOW	65/34	300	10/8	90	.420	4	BK, W, R, G	1.50	3.1
4-8024-89-91W	16	4	SJOW	65/34	300	13	90	.420	2	BK, W, R, G	1.50	1.9
4-8047-99-92	12	7	***	65/30	300	14	60	.775	4	R, BK, OE, W, G, BE, BN	2.55	13.0
4-8047-89-92	12	7	***	65/30	300	14	60	.775	2	R, BK, OE, W, G, BE, BN	2.55	6.3

HEAVY DUTY / TYPE: SOW

- Neoprene Jacket
- 600 V Cord
- UL Listed
- CUL Listed
- CSA Certified

PART NUMBER	AWG SIZE	# COND.	UL TYPE	STRAND	MAX. VOLT	AMPS	TEMP. RATING	CORD O.D.	RET. LGTH. FT.	PRIMARY COND. COLOR	COIL O.D.	LBS / CORD
4-8063-00-91W	18	3	SOW	41/34	600	10/7	90	.385	4	BK, W, G	1.31	2.52
4-8063-89-91W	18	3	SOW	41/34	600	10/7	90	.385	2	BK, W, G	1.31	1.6
4-8064-00-91W	18	4	SOW	41/34	600	7/5.6	90	.415	4	BK, W, R, G	1.50	3.03
4-8064-89-91W	18	4	SOW	41/34	600	7/5.6	90	.415	2	BK, W, R, G	1.50	1.8
4-8093-00-91W	16	3	SOW	65/34	600	13/10	90	.415	4	BK, W, G	1.50	3.1
4-8093-89-91W	16	3	SOW	65/34	600	13/10	90	.415	2	BK, W, G	1.50	1.5
4-8094-00-91W	16	4	SOW	65/34	600	10/8	90	.445	4	BK, W, R, G	1.63	4.5
4-8094-89-91W	16	4	SOW	65/34	600	10/8	90	.445	2	BK, W, R, G	1.63	2.4
4-8095-00-91W	16	5	SOW	65/34	600	8	90	.525	4	BK, W, R, G, OE	1.81	4.9
4-8095-89-91W	16	5	SOW	65/34	600	8	90	.525	2	BK, W, R, G, OE	1.81	2.8
4-8096-00-91W	16	6	SOW	65/34	600	8	90	.575	4	BK, W, R, G, OE, BE	2.03	6.2
4-8096-89-91W	16	6	SOW	65/34	600	8	90	.575	2	BK, W, R, G, OE, BE	2.03	3.4
4-8097-00-91W	16	7	SOW	65/34	600	7	90	.575	4	BK, W, R, G, OE, BE, Y	2.03	6.5
4-8097-89-91W	16	7	SOW	65/34	600	7	90	.575	2	BK, W, R, G, OE, BE, Y	2.03	3.5
4-8027-89-91W	6/16-1/14	7	SOW	65/34-41/30	600	10.5/7	90	.600	2	BK, Y, R, G, BN, BE, W	2.25	3.9
4-8027-00-91W	6/16-1/14	7	SOW	65/34-41/30	600	10.5/8	90	.600	4	BK, Y, R, G, BN, BE, W	2.25	7.9
4-8099-00-91W	16	8	SOW	65/34	600	9.1/7	90	.605	4	BK, W, R, G, OE, BE, Y, BN	2.10	7.4
4-8099-89-91W	16	8	SOW	65/34	600	9.1/7	90	.605	2	BK, W, R, G, OE, BE, Y, BN	2.10	4.1
4-8032-00-91W	14	2	SOW	41/30	600	18	90	.520	4	BK, W	1.81	4.0
4-8032-89-91W	14	2	SOW	41/30	600	18	90	.520	2	BK, W	1.81	2.5
4-8033-00-91W	14	3	SOW	41/30	600	18/15	90	.545	4	BK, W, G	2.00	5.9
4-8033-89-91W	14	3	SOW	41/30	600	18/15	90	.545	2	BK, W, G	2.00	3.0
4-8034-00-91W	14	4	SOW	41/30	600	15/12	90	.590	4	BK, W, R, G	2.06	6.3
4-8034-89-91W	14	4	SOW	41/30	600	15/12	90	.590	2	BK, W, R, G	2.06	3.17
4-8042-00-91W	12	2	SOW	65/30	600	25	90	.600	4	BK, W	2.25	6.7
4-8042-89-91W	12	2	SOW	65/30	600	25	90	.600	2	BK, W	2.25	3.8
4-8043-00-91W	12	3	SOW	65/30	600	25/20	90	.630	4	BK, W, G	2.25	7.0
4-8043-89-91W	12	3	SOW	65/30	600	25/20	90	.630	2	BK, W, G	2.25	4.2
4-8044-00-91W	12	4	SOW	65/30	600	20/16	90	.680	4	BK, W, R, G	2.38	9.0
4-8044-89-91W	12	4	SOW	65/30	600	20/16	90	.680	2	BK, W, R, G	2.38	4.8
4-8056-00-91	2/12-4/18	6	**	41/34-65/30	600	5.6/16	60	.610	4	BK, W, G, R, BK, W	2.25	7.8

FEATURES OF WHITNEY BLAKE RETRACTILE CORDS:

- Stranded, bare copper conductors separator over conductors
- Color-coded rubber insulation
- Separator over core
- Neoprene® jacket overall 60°C (140°F), W Rated 90°C
- Ends: Six-inch blunt cut
- Surface printed for identification where applicable

NOTES: (for these 3 charts)

- * UL Style 4329 as appliance wiring. Not CSA Certified.
- ** Not listed by UL or CSA Certified
- *** Rubber Jacket

